

KNEADER MACHINERY CO., LTD.

密閉式混合機

INTENSIVE MIXER

橡膠、塑膠及化學工業原料混合加工用
Compounding For Rubber、Plastic & Chemical Industries



油壓控制排料門組 Hydraulic discharge door



防漏活塞溫度控制 Temp. sensor for seal



說明

- 攪拌軸：以特殊合金鋼鑄造，設計為二翼式，翼尖熔接耐模耗材料及全部表面鍍硬質鉻及拋光處理，翼根設計有冷熱媒傳導迴路，熱傳導效果良好。
Rotors: Two wings design with good cooling design. Excellent cooling ability. Anti-wearing treatment on the surface.
- 混合室：以中碳鋼板焊接組合加工製成，混料接觸面均經鍍硬質鉻及拋光處理，中間槽為鑽孔式迴路，具有優良之熱傳導。
Chamber: Drill hole type jacket. Excellent cooling ability. Material contact surface: Hard chrome plating and fine polish.
- 卸料門：設計為落門式，結構堅固，防漏效果良好。
Discharge door: Excellent sealing. No material leakage.
- 加壓錘：以垂直空壓缸操作，達到壓料在混合室內良好混練效果。
Ram: Drive by air cylinder. Good mixing and dispersion quality.

規格明細 (Specification):

| 機 型 Model | 混練容量 Mixing capa. | 主馬力 Main power | 油壓馬力 Hydraulic power | 注油器馬力 Lubricator | 溫度控制 Temp. control | 集塵機馬力 Dust collector |
|------------------|----------------------|-------------------|-------------------------|---------------------|-----------------------|-------------------------|
| KD-IM-50 | 50 L | 150-200 HP | 3 HP | 1/2 HP | 自動/Auto | 1/2 HP |
| KD-IM-75 | 75 L | 200-400 HP | 3 HP | 1/2 HP | 自動/Auto | 1 HP |
| KD-IM-100 | 100 L | 300-500 HP | 5 HP | 1/2 HP | 自動/Auto | 1 HP |

Optional: PLC control, Touch screen panel, Auto weighting system turnkey / Inverter motor with Inverter, DC motor

利拿機械工業股份有限公司

台灣一廠：台南市永康區蔦松三街81巷2號 台灣二廠：台南市永康區蔦松三街81巷11號

Factory 1: No. 2, Ln. 81, Niaosong 3rd St., Yong Kang Dist., Tainan City, Taiwan

Factory 2: No. 11, Ln. 81, Niaosong 3rd St., Yong Kang Dist., Tainan City, Taiwan

Tel: +886-6-2438586

Fax: +886-6-2434205

[HTTP://WWW.KNEADER.COM.TW](http://www.kneader.com.tw) E-MAIL: SALES@KNEADER.COM.TW